

according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier NEXLER STYROPUK FUNDAMENT

Substance / mixture mixture

UFI AJU1-204N-Q00X-1A11

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Mixture's intended use

Foam for gluing and sealing.

Main intended use

PC-ADH-2 Adhesives and sealants - building and construction works (except cement based

adhesives)

### Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

### 1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name NEXLER sp. z o.o.

Address Łużycka 6, Gdynia, 81-537

Poland

Identification number (CRN)191528483VAT Reg NoPL5862073821Phone+48 58 781 45 85E-mailinfo@nexler.comWeb addresswww.nexler.com

Competent person responsible for the safety data sheet

Name NEXLER sp. z o.o. E-mail info@nexler.com

### 1.4. Emergency telephone number

National Health Service (NHS) 111

National poisoning information centre Scotland, NHS 24: 111

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H229, H222 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 Lact., H362

STOT RE 2, H373 (the respiratory system) (inhalation)

Aquatic Chronic 4, H413

Full text of all classifications and hazard statements is given in the section 16.

### Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

#### Most serious adverse effects on human health and the environment

Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause an allergic skin reaction. May cause harm to breast-fed children. Harmful if inhaled. May cause damage to the respiratory system through prolonged or repeated exposure if inhaled. May cause long lasting harmful effects to aquatic life. The product has been classified as hazardous to the aquatic environment in category 4 (H413) of chronic toxicity based on the results of tests on polyurethane foams containing 30% MCCP, commissioned by FEICA.

according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

1.0 Revision date Version

#### 2.2. Label elements

# Hazard pictogram







#### Signal word

Danger

#### **Hazardous substances**

methylenediphenyl diisocyanate, isomers and homologues alkanes, C14-17, chloro

### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

May cause damage to the respiratory system through prolonged or repeated H373

exposure if inhaled.

H413 May cause long lasting harmful effects to aquatic life.

# **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container to by disposing in a hazardous waste receptacle.

# Supplemental information

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

# Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

#### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

	CHVII OHIIICHC			
Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 9016-87-9 Registration number: - [REACH art. 2 (9)]	methylenediphenyl diisocyanate, isomers and homologues	30-60	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 (the respiratory system) (inhalation) Specific concentration limit: Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335: C ≥ 5% Resp. Sens. 1, H334: C ≥ 0.1 %	3, 6
Index: 602-095-00-X CAS: 85535-85-9 EC: 287-477-0 Registration number: 01-2119519269-33	alkanes, C14-17, chloro	<15	Lact., H362 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10) EUH066	4, 5, 7
Index: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2 Registration number: 01-2119485395-27	isobutane	5-10	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	1
Index: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8 Registration number: 01-2119472128-37	dimethyl ether	5-10	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	1, 2
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 Registration number: 01-2119486944-21	propane	1-5	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	1

### Notes

Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- 2 A substance for which exposure limits are set.
- 3 Substance for which biological limit values exist.
- 4 Substance of very high concern SVHC.
- 5 Persistent, bioaccumulative and toxic or very persistent and very bioaccumulative
- 6 The use of the substance is restricted by Annex XVII of REACH Regulation
- 7 Substance of unknown or variable composition, complex reaction products or biological materials UVCB.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

Full text of all classifications and hazard statements is given in the section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

#### If on skin

Remove contaminated clothes. Wash the skin with a mild solvent such as acetone, then with soap and water.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

#### If swallowed

Rinse out the mouth with clean water. In the event of issues, find medical help.

# 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

#### If on skin

May cause an allergic skin reaction.

#### If in eyes

Causes serious eye irritation.

### If swallowed

Irritation, nausea.

# 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

# Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

## Unsuitable extinguishing media

Water - full jet.

# 5.2. Special hazards arising from the substance or mixture

Extremely flammable product, in the event of fire it may emit dangerous gases: nitrogen oxides, carbon monoxide, isocyanates and trace amounts of cyanides may be formed. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage. In the event of an ambient fire, there is a risk of pressure build-up and containers bursting.

### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

vexler

according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not eat, drink or smoke when using this product. Do not spray on an open flame or other ignition source. Avoid contact during pregnancy and while nursing. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

#### 7.3. Specific end use(s)

not available

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

# **United Kingdom**

# EH40/2005 Workplace exposure limits (Fourth Edition 2020)

		<u> </u>
Substance name (component)	Туре	Value
	WEL 8h	766 mg/m <sup>3</sup>
dimethyl other (CAS, 11E 10.6)	WEL 8h	400 ppm
dimethyl ether (CAS: 115-10-6)	WEL 15min	958 mg/m <sup>3</sup>
	WEL 15min	500 ppm

#### **Biological limit values**

### **United Kingdom**

# EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Name	Parameter	Value	Tested material	Time of sampling
methylenediphenyl diisocyanate, isomers and homologues (CAS: 9016-87-9)	isocyanate-derived diamine	1 µmol/mol creatinine	Urine	End of exposure or end of shift

#### **DNEL**

alkanes, C14-17	alkanes, C14-17, chloro					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source	
Consumers	Dermal	28.75 mg/kg bw/day	Chronic effects systemic			
Consumers	Inhalation	2 mg/m <sup>3</sup>	Chronic effects systemic			



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

alkanes, C14-17, chloro					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	47.9 mg/kg bw/day	Chronic effects systemic		
Workers	Inhalation	6.7 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Oral	0.58 mg/kg bw/day	Chronic effects systemic		

#### **PNEC**

alkanes, C14-17, chloro	alkanes, C14-17, chloro					
Route of exposure	Value	Value determination	Source			
Marine water	0.2 μg/l					
Microorganisms in sewage treatment	80 mg/l					
Freshwater sediment	13 mg/kg of dry substance of sediment					
Sea sediments	2.6 mg/kg of dry substance of sediment					
Soil (agricultural)	11.9 mg/kg of dry substance of soil					
Drinking water	1 μg/l					
Food chain	10 mg/kg of food					

### 8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

# Eye/face protection

Protective goggles.

# Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

## **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

### Thermal hazard

Data not available.

### **Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state liquid
Colour yellow
Odour characteristic
Melting point/freezing point not applicable
Boiling point or initial boiling point and boiling range not applicable
Flammability inflammable



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

Lower and upper explosion limit

bottom 1.5 % upper 16 %

Flash point not applicable
Auto-ignition temperature not determined

dimethyl ether (CAS: 115-10-6) 226 °C

Decomposition temperature not applicable PH reacts with water Kinematic viscosity not applicable

Solubility in water reacts with water
Partition coefficient n-octanol/water (log value) does not apply to mixtures

Vapour pressure <0.7 MPa at 20 °C

Density and/or relative density

Density 1 g/cm<sup>3</sup> at 20 °C

Relative vapour density >1

Particle characteristics applies to solids

#### 9.2. Other information

not available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts with nucleophiles (amines, alcohols, water, etc.)

#### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reacts exothermically with amines and alcohols, releasing CO2 with water, which may cause pressure increase in closed containers and their bursting.

### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated. Avoid direct sunlight and moisture.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses.

### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

### **Acute toxicity**

Harmful if inhaled.

alkanes, C14-17, chloro						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD50		>4000 mg/kg bw		Rat (Rattus norvegicus)	F/M

methylenediphenyl diisocyanate, isomers and homologues						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD50	OECD 401	>2000 mg/kg bw		Rat (Rattus norvegicus)	F/M



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

methylenediphenyl diisocyanate, isomers and homologues						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Dermal	LD50	OECD 402	>9400 mg/kg bw		Rat (Rattus norvegicus)	F/M
Inhalation	LC50	OECD 403	0.31 mg/l of air	4 hours	Rat (Rattus norvegicus)	F/M

### Skin corrosion/irritation

Causes skin irritation.

alkanes, C14-17, chloro					
Route of exposure	Result	Method	Exposure time	Species	
Dermal	Slightly irritating	OECD 404	4 hours	Rabbit	

methylenediphenyl diisocyanate, isomers and homologues					
Route of exposure	Result	Method	Exposure time	Species	
Dermal	Irritating	OECD 404	4 hours	Rabbit	

# Serious eye damage/irritation

Causes serious eye irritation.

alkanes, C14-17, chloro					
Route of exposure	Result	Method	Exposure time	Species	
Eye	Slightly irritating			Rabbit	

methylenediphenyl diisocyanate, isomers and homologues								
Route of exposure Result Method Exposure time Species								
Eye	Eye Slightly irritating OECD 405 Rabbit							

# Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

methylenediphenyl diisocyanate, isomers and homologues								
Route of exposure	Result	Method	Exposure time	Species	Sex			
Dermal	Sensitizing	OECD 429		Mouse				
Inhalation	Sensitizing			Guinea-pig (Cavia aperea f. porcellus)	F			

# Germ cell mutagenicity

Based on available data the classification criteria are not met.

# Carcinogenicity

Suspected of causing cancer.

methylenediphenyl diisocyanate, isomers and homologues								
Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	
Inhalation (aerosols)		OECD 453	6 mg/m <sup>3</sup>	2 years	Tumor formation	Rat (Rattus norvegicus)	F/M	



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

#### Reproductive toxicity

May cause harm to breast-fed children.

# Toxicity for specific target organ - single exposure

May cause respiratory irritation.

methylenediphenyl diisocyanate, isomers and homologues							
Route of exposure Parameter Value Result Species Sex							
Inhalation	Inhalation Irritating						

#### Toxicity for specific target organ - repeated exposure

May cause damage to the respiratory system through prolonged or repeated exposure if inhaled.

alkanes, C14-17, chloro								
Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	
Oral	NOAEL	OECD 408	23 mg/kg bw/day	13 weeks	Systemic effects	Rat (Rattus norvegicus)	F/M	

methylenedip	methylenediphenyl diisocyanate, isomers and homologues								
Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex		
Inhalation					Causes damage				

# Repeated dose toxicity

methylenedip	methylenediphenyl diisocyanate, isomers and homologues									
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex			
Inhalation (aerosols)	LOAEC	Local effects	OECD 453	1 mg/m³	2 years	Rat (Rattus norvegicus)	F/M			
Inhalation (aerosols)	NOAEC	Local effects	OECD 453	0.2 mg/m <sup>3</sup>	2 years	Rat (Rattus norvegicus)	F/M			

### **Aspiration hazard**

Based on available data the classification criteria are not met.

# 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

May cause long lasting harmful effects to aquatic life.

# **Acute toxicity**

alkanes, C14-17, chloro									
Parameter	Method	Value	Exposure time	Species	Environme nt	Value determination			
EC50	OECD 202	5.9 μg/l	48 hours	Aquatic invertebrates (Daphnia magna)					
LC50	OECD 203	>10000 mg/l	96 hours	Fish (Alburnus alburnus)					



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

alkanes, C14-17, chloro								
Parameter	Method	Value	Exposure time	Species	Environme nt	Value determination		
EC50	OECD 201	>3.2 mg/l	96 hours	Algae (Raphidocelis subcapitata)				
NOEC	OECD 201	0.1 mg/l	96 hours	Algae (Raphidocelis subcapitata)				
NOEC	OECD 209	>2000 mg/l	3 hours	Aquatic microorganisms	Activated sludge			

methylened	iphenyl diisocya	nate, isomers and	homologues			
Parameter	Method	Value	Exposure time	Species	Environme nt	Value determination
EL 50	OECD 209	>1000 mg/l	3 hours	Aquatic microorganisms	Activated sludge	
EC50	OECD 207	>1000 mg/kg of dry substance of soil		Invertebrates (Eisenia fetida)		
LL 50	OECD 203	>100 mg/l	96 hours	Fish (Danio rerio)		
EL 50	OECD 202	3.7 mg/l	48 hours	Aquatic invertebrates (Daphnia magna)		Read-across
EL 50	OECD 201	>100 mg/l	72 hours	Algae (Desmodesmus subspicatus)		

# **Chronic toxicity**

alkanes, C14-17	alkanes, C14-17, chloro								
Parameter	Method	Value	Exposure time	Species	Environmen t				
NOEC	OECD 204	4.5 mg/l	60 days	Fish (Oncorhynchus mykiss)					
NOEC	OECD 202	8.7 μg/l	21 days	Aquatic invertebrates (Daphnia magna)					

# 12.2. Persistence and degradability

The product is partially biodegradable.

# **Biodegradability**

alkanes, C14-17, chloro							
Parameter	Method	Value	Exposure time	Environment	Result		
	OECD 301D	27 %	28 days		Hardly biodegradable		

# 12.3. Bioaccumulative potential

Bioaccumulation is not expected.

alkanes, C14-17, chloro						
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow		5.47≤≤8.01				



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

methylenediphenyl diisocyanate, isomers and homologues						
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
BCF	OECD 305	92	28 days	Fish (Cyprinus carpio)		

#### 12.4. Mobility in soil

The product is insoluble in water and does not show mobility in soil.

alkanes, C14-17, chloro				
Parameter	Value	Environment	Temperature	Value determination
Log Koc	5.77			QSAR

#### 12.5. Results of PBT and vPvB assessment

Based on Decision D(2021)4569-DC, chloroalkanes, C14-17 are assigned PBT and vPvB properties. A 28-day aquatic toxicity study of polyurethane foams containing 30% MCCP, commissioned by FEICA, showed no presence of dissolved MCCP in water.

#### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

#### 12.7. Other adverse effects

Data not available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Danger of environmental contamination, follow the applicable waste disposal regulations. Store unused product and contaminated packaging in closed containers for waste collection and hand over for disposal to a specialized company authorized to conduct such activity. Do not pour unused product into drains. It must not be disposed of together with municipal waste. Empty packaging can be used for energy in a waste incineration plant or collected in a landfill with an appropriate classification. Perfectly cleaned packaging can be recycled. The classification of waste may change depending on where it is generated.

# Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

# **SECTION 14: Transport information**

### 14.1. UN number or ID number

UN 1950

### 14.2. UN proper shipping name

**AEROSOLS** 

### 14.3. Transport hazard class(es)

2 Gases

#### 14.4. Packing group

not relevant

# 14.5. Environmental hazards

No.

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

# 14.7. Maritime transport in bulk according to IMO instruments

not relevant



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

#### **Additional information**

Hazard identification No.

UN number Classification code Safety signs



5F 2.1



# Road transport - ADR

Special provisions 190, 327, 344, 625

Limited quantities 1 L Excepted quantities E0

**Packaging** 

Packing instructions P207, LP200 Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9
Transport category 2
Tunnel restriction code (D)

Special provision for

packages V14

loading, unloading and handling CV9, CV12

operation S2

Railway transport - RID

Special provisions 190, 327, 344, 625

Excepted quantities E0

**Packaging** 

Packing instructions P207, LP200 Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9
Transport category 0

Special provision for

packages W 14

loading, unloading and handling CW 9, CW 12

Air transport - ICAO/IATA

Packaging instructions for limited amount Y203
Packaging instructions passenger 203
Cargo packaging instructions 203

Marine transport - IMDG

EmS (emergency plan) F-D, S-U MFAG 620



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

1.0 Revision date Version

#### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Clean Air Act 1993 as amended. The Aerosol Dispensers (Amendment) Regulations 2018. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Public health act 1961. Environmental Protection Act 1990 as amended. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

# Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

	phenyl diisocyanate, isomers and homologues
Restriction	Conditions of restriction
56	1. Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging:  (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC (*********);
	(b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures: "— Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
	— Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
	<ul> <li>This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used."</li> </ul>
	2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.
74	1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:
	(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or
	(b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture
	(s). 2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or
	(b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".  3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.
	4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:  (a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).  (b) the training elements in points (a) and (b) of paragraph 5 for the following uses:  — handling open mixtures at ambient temperature (including foam tunnels);
	<ul> <li>spraying in a ventilated booth;</li> <li>application by roller;</li> <li>application by brush;</li> <li>application by dipping and pouring;</li> </ul>
	<ul> <li>mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore;</li> <li>cleaning and waste;</li> </ul>



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date 1.0 Version

methylenedinhenyl diisocyanate isomers and homologues

metnylenealpr	nenyl diisocyanate, isomers and homologues
Restriction	Conditions of restriction
	— any other uses with similar exposure through the dermal and/or inhalation route;
	(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:
	<ul><li>handling incompletely cured articles (e.g. freshly cured, still warm);</li></ul>
	<ul><li>foundry applications;</li></ul>
	<ul> <li>maintenance and repair that needs access to equipment;</li> </ul>
	— open handling of warm or hot formulations (> 45 °C);
	— spraying in open air, with limited or only natural ventilation (includes large industry working halls)
	and spraying with high energy (e.g. foams, elastomers);
	— and any other uses with similar exposure through the dermal and/or inhalation route.
	5. Training elements:
	(a) general training, including on-line training, on:
	— chemistry of diisocyanates;
	<ul> <li>toxicity hazards (including acute toxicity);</li> </ul>
	— exposure to diisocyanates;
	<ul> <li>occupational exposure limit values;</li> </ul>
	— how sensitisation can develop;
	— odour as indication of hazard;
	— importance of volatility for risk;
	viscosity, temperature, and molecular weight of diisocyanates;
	— personal hygiene;
	<ul> <li>personal protective equipment needed, including practical instructions for its correct use and its</li> </ul>
	limitations;
	— risk of dermal contact and inhalation exposure;
	- risk in relation to application process used;
	— skin and inhalation protection scheme;
	- ventilation;
	— cleaning, leakages, maintenance;
	— discarding empty packaging;
	— protection of bystanders;
	- identification of critical handling stages;
	— specific national code systems (if applicable);
	— behaviour-based safety;
	— certification or documented proof that training has been successfully completed
	(b) intermediate level training, including on-line training, on:
	— additional behaviour-based aspects;
	— maintenance;
	— management of change;
	— evaluation of existing safety instructions;
	<ul><li>risk in relation to application process used;</li></ul>
	certification or documented proof that training has been successfully completed
	(c) advanced training, including on-line training, on:
	— any additional certification needed for the specific uses covered;
	— spraying outside a spraying booth;
	— open handling of hot or warm formulations (> 45 °C);
	— certification or documented proof that training has been successfully completed
	6. The training shall comply with the provisions set by the Member State in which the industrial or
	professional user(s) operate. Member States may implement or continue to apply their own national
	requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements
	set out in paragraphs 4 and 5 are met.
	7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with
	training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the
	Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into
	consideration the specificity of the products supplied, including composition, packaging, and design.
	8. The employer or self-employed shall document the successful completion of the training referred
	to in paragraphs 4 and 5. The training shall be renewed at least every five years.
	9. Member States shall include in their reports pursuant to Article 117(1) the following information:
	(a) any established training requirements and other risk management measures related to the
	industrial and professional uses of diisocyanates foreseen in national law;
	(b) the number of cases of reported and recognised occupational asthma and occupational respiratory
1	and dermal diseases in relation to disocyanates;
I	(c) national exposure limits for diisocyanates, if there are any;



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

methylenediphenyl diisocyanate, isomers and homologues

Restriction	Conditions of restriction
	(d) information about enforcement activities related to this restriction.  10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

### **SECTION 16: Other information**

A list of standard	risk phrases used in the safety data sheet
H220	Extremely flammable das

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to the respiratory system through prolonged or repeated exposure if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

# Guidelines for safe handling used in the safety data sheet

P102	Keep out	of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container to by disposing in a hazardous waste receptacle.

# A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

# Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures

EC Identification code for each substance listed in EINECS

EC50 Concentration of a substance when it is affected 50% of the population



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

EINECS European Inventory of Existing Commercial Chemical Substances

EL<sub>50</sub> Effective Loading for 50% of the tested organisms

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

LU50 Lethal Loading for 50% of tested organisms
LOAEC Lowest observed adverse effect concentration

log Kow Octanol-water partition coefficient

NOAEC No observed adverse effect concentration

NOAEL No observed adverse effect level NOEC No observed effect concentration OEL Occupational Exposure Limits

PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

Press. Gas (Comp.)

Gas under pressure: compressed gas

Press. Gas (Diss.)

Gas under pressure: dissolved gas

Press. Gas (Liq.)

Gas under pressure: liquefied gas

Press. Gas (Ref. Liq.) Gas under pressure: refrigerated liquefied gas

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Acute Tox. Acute toxicity
Aerosol Aerosol

Aquatic Acute Hazardous to the aquatic environment

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Carc. Carcinogenicity
Eye Irrit. Eye irritation
Flam. Gas Flammable gas
Lact. Lactation

Press. Gas Gases under pressure
Resp. Sens. Respiratory sensitization

Skin Irrit. Skin irritation
Skin Sens. Skin sensitization

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

**Training guidelines** 



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER STYROPUK FUNDAMENT**

Creation date 27th November 2023

Revision date Version 1.0

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

#### **Recommended restrictions of use**

not available

## Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

#### More information

Classification procedure - calculation method and based on test results.

#### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.