

## DECLARATION OF PERFORMANCE No. 181-CPR-2024

1. Unique identification code:

Self-adhesive membrane

## NEXLER Membrana SP (2024/1)

- 2. Intended use or uses:
  - a) damp-proof and waterproof insulation in buildings, including underground structural elements, subject to reaction-to-fire requirements,
  - b) damp-proof and waterproof insulation in buildings, including underground structural elements.
- 3. The manufacturer:

NEXLER sp. z o.o. ul. Łużycka 6 81-537 Gdynia, Poland tel., fax +48 58 781 45 85 e-mail: info@nexler.com

 Systems of assessment and verification of constancy of performance:

system 2+ – for the applications: b system 3 – for the applications: a

Harmonized standard:

EN 13967:2012

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification (Polskie Centrum Badań i Certyfikacji S.A.)

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Reaction to fire	Class E	
Watertightness	≥ 60 kPa (method B)	
Maximum tensile force: - longitudinal - extension	≥ 200 N/50 mm ≥ 100 %	
- transversal - extension	≥ 200 N/50 mm ≥ 100 %	
Resistance to static loading	≥ 10 kg (method B)	
Resistance to impact	≥ 350 mm (method A)	EN 13967:2012
Resistance to tearing: - longitudinal - transversal	≥ 130 N ≥ 130 N	
Resistance of the joint: - longitudinal - transversal	≥ 200 N/50 mm ≥ 200 N/50 mm	
Durability: - durability after artificial ageing, watertightness	≥ 60 kPa (method B)	
<ul> <li>durability against chemical, watertightness</li> </ul>	≥ 60 kPa (method B)	
Dangerous substances	NPD	

The performance of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Kenrad Liberda

Konrad Liberda

in Gdynia, on 14.02.2024