

DECLARATION OF PERFORMANCE No. 006-CPR-2024

1. Unique identification code:

Top layer bitumen membrane

W 400/1200 (2024/1)

- 2. Intended use or uses:
 - a) waterproofing of roofs,
 - b) waterproofing of roofs, which is the subject to fire reaction test.
- The manufacturer:

NEXLER sp. z o.o. ul. Łużycka 6, 81-537 Gdynia, Poland tel., fax +48 58 781 45 85 e-mail: info@nexler.com

 Systems of assessment and verification of constancy of performance:

system 2+ – for the applications: a system 3 – for the applications: b

Harmonized standard:

EN 13707:2004+A2:2009

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification (Polskie Centrum Badań i Certyfikacji S.A.)

1486 The Research and Development Centre for Building Insulation Industry (Centralny Ośrodek Badawczo-Rozwojowy Przemysłu Izolacji Budowlanej)

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Resistance to external fire exposure	NPD	
Reaction to fire	Class E	
Watertightness	≥ 10 kPa (method A)	
Maximum tensile force: - longitudinal - extension	500 ± 300 N/50mm (3 ± 2) %	
- transversal - extension	400 ± 200 N/50mm (3 ± 2) %	
Resistance to root penetration	NPD	
Resistance to static loading	NPD	
Resistance to impact	NPD	
Resistance to tearing: - longitudinal - transversal	70 ± 30 N 70 ± 30 N	EN 13707:2004+A2:2009
Resistance of the joint	NPD	
Durability: flow resistance at elevated temperature	(80 ± 10)°C	
Flexibility	≤ 0°C	
Dangerous substances	NPD	

The performances of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Kenrad Liberda

Konrad Liberda

in Gdynia, on 11.01.2024