



AQUAMINERAL

mineral-polymer waterproofing



***Damp proof isolation
and waterproofing***

Foundations, cellars

Wet rooms

Balconies and terraces

Tanks



AQUAMINERAL

mineral-polymer waterproofing



AQUAMINERAL 1K Ultra

One-component sealing micro-mortar

- ✓ Damp proof and waterproof insulation of: foundations, basements in old and new buildings, tanks, etc.
- ✓ Indoor waterproofing tanking type
- ✓ Horizontal waterproofing

Consumption: ca. 1,5 kg/m²

Drying time: 12 h

Has Hygienic Certificate

Available packaging: 15 kg



AQUAMINERAL 2K Ultra

Two-component, highly elastic sealing micro-mortar

Damp proofing and waterproofing of:

- ✓ Foundations, basements in old and new buildings
- ✓ Wet rooms
- ✓ Swimming pools and tanks
- ✓ Terraces and balconies

Consumption: ca. 1,5 kg/m²

Drying time: 12 h

Available packaging: 40 kg



AQUAMINERAL 2K

Two-component sealing micro-mortar

Damp proofing and waterproofing of:

- ✓ Foundations, basements in old and new buildings
- ✓ Terraces and balconies
- ✓ Wet rooms

Consumption: ca. 1,5 kg/m²

Drying time: up to 12 h

Has Hygienic Certificate

Available packaging: 20 kg



AQUAMINERAL 2K Pro

Chemically resistant, two-component sealing micro-mortar

For waterproofing and anti-corrosion protection of concrete substrates:

- ✓ Storage tanks for water and other fluids
- ✓ Sewage treatment and biogas plants
- ✓ Ceilings, walls and foundations, etc.

Consumption: ca. 1,5 kg/m²

Drying time: 12 h

Available packaging: 19 kg





Izofol

Liquid foil

- For waterproof coatings in rooms exposed to water and moisture, e.g. in bathrooms, laundries, kitchens
- Waterproofing in underfloor heating systems

Consumption: ca. 0,8 - 1,0 kg/m²

Drying time: up to 24 h

Has Hygienic Certificate

Available packaging: 4, 7, 12 kg



Izofol Flex

Highly elastic liquid foil

- For waterproof coatings in rooms exposed to water and moisture, e.g. in bathrooms, laundries, kitchens, balconies and stairs
- Waterproofing in underfloor heating systems

Consumption: ca. 0,8 - 1,0 kg/m²

Drying time: up to 24 h

Has Hygienic Certificate

Available packaging: 4, 7, 12 kg



Gruntofol

Priming emulsion

- Priming of concrete, aerated concrete, cement plasters, plasterboards, wood, wood-like boards and other absorbent substrates

Consumption: 0,2 - 0,25kg/m²

Drying time: ca. 1 h

Has Hygienic Certificate

Available packaging: 5 kg

